PRODUCT DATASHEET

Hotel Lock Series SML-HTL-003 – 006

RFID Card Mortise Lock, 201 mm Panel

Model range: SML-HTL-003 · SML-HTL-004 · SML-HTL-005 · SML-HTL-006

SML-HTL-003 to SML-HTL-006 are zinc-alloy RFID card mortise locks with a taller 201 mm panel, for guest room doors where a longer lever and a larger credential area are preferred. Guests unlock with a room card or the mechanical key override, on either a hotel-system or a stand-alone PCB.

They share the mortise, electronics and card system of the SML-HTL-001 series, so a property can mix both panel sizes across floors without running two access-control systems.



SML-HTL-006 in black; the same 201 mm panel is available in four finishes.

At a Glance

Unlock way	RFID card / mechanical key
PCB type	Hotel/stand-alone
Panel size	L201 × W71 × H22 mm
Panel material	Zinc alloy
Default mortise	Single latch mini mortise
Net weight	3 kg

Key Features

- **Card and key entry:** RFID card plus a mechanical key override, with M1 cards issued at the front desk or programmed at the lock.
- **Mortise options:** Single latch mini mortise as standard, with 2S/4S reversal, 3S anti-theft and 3585/4585 aluminium-door bodies available.
- **Panel finishes:** One 201 × 71 mm zinc-alloy panel in golden, coffee gold, black or red bronze; the taller panel gives more space for a logo and a card reader.
- **OEM/ODM:** Custom logo, packaging, firmware behaviour and finish on request; samples in 7–10 days.

Series Selection

Four finishes share one 201 × 71 mm panel and one mechanical platform. Finish is the only difference between the models, so a sample of one finish represents the range.

Model	Finish	Panel size	Material	Notes

SML-HTL-003	Golden	L201 × W71 × H22 mm	Zinc alloy	Standard body
SML-HTL-004	Coffee gold	L201 × W71 × H22 mm	Zinc alloy	Same body, alternate finish
SML-HTL-005	Red bronze	L201 × W71 × H22 mm	Zinc alloy	Same body, alternate finish
SML-HTL-006	Black	L201 × W71 × H22 mm	Zinc alloy	Same body, alternate finish

Technical Specifications

Unlock way	RFID card / mechanical key
Credential	M1 card (13.56 MHz) issued at the front desk or programmed at the lock
PCB type	Hotel/stand-alone
Panel size	L201 × W71 × H22 mm
Panel material	Zinc alloy
Finish options	Golden, Coffee gold, Red bronze, Black
Default mortise	Single latch mini mortise
Mortise options	Single latch mini (standard) · 2S / 4S reversal · 3S anti-theft · 3585 / 4585 aluminium
Net weight	3 kg
Power supply	Battery operated — batteries not included
Certifications	CE, FCC, RoHS; ISO 9001 quality system
Warranty	14 months
Lead time	3–7 working days
MOQ	500 pcs for standard models; negotiable for OEM/ODM

Table 1 Specifications. Values apply to the standard configuration; project-specific options are confirmed at quotation.

Mortise and Door Compatibility

Both series ship with a single latch mini mortise. The mortise is the part that defines the door preparation, so it is selected before the panel and finish.



Single latch mini mortise, standard on both series.

Standard: single latch mini mortise. Available in the family: 2S and 4S reversal mortise bodies for fire-rated doors, 3S anti-theft bodies, and 3585/4585 bodies for aluminium doors.

Door thickness, cut-out and backset follow the mortise chosen for the project; confirm the mortise and door specification with sales before ordering. Handle orientation defaults to right-hand inside and must be stated on the order.

Card System and PCB Options

Two PCB options share the same mechanical platform. A hotel-system PCB works with front-desk issued cards and hotel management software, so access rights, expiry and audit sit in the property system. A stand-alone PCB issues and manages cards at the lock itself, which suits smaller properties and offline rooms. The same panel and mortise are used either way, so the choice can be made per building.

Ordering and Support

Specify the model, finish, mortise, PCB type, handle orientation and quantity when requesting a quotation. Samples ship in 7–10 days; mass production takes 20–30 days.

Incoterms	FOB Shenzhen · CIF · DDP · EXW
Payment terms	T/T 30% deposit + 70% before shipment · L/C at sight · Trade Assurance
Sample lead time	7–10 days
Sales	sales@smartmortiselock.com
Support	sales@smartmortiselock.com
Website	smartmortiselock.com

Specifications describe the standard configuration and are subject to change without notice. Door thickness, cut-out dimensions and battery configuration are confirmed per project; batteries are not included with the lock.